


ΣΤΗΡΙΓΜΑΤΑ HI-T ΒΤ ΜΕ ΣΥΜΠΑΓΕΣ ΛΑΣΤΙΧΟ Pipe clamps with solid rubber - 10521

Φ (mm) min-max	Cu (mm) Φ	Fe (inch)	Cu (inch)	PVC	ΣΠΕΙΡ.	ΚΙΒ.	ΣΥΣΚ.
15-19	Φ 18	3/8"			M8	150	25
19-23	Φ 22	1/2"	7/8"		M8	150	25
26-30	Φ 28	3/4"	1 1/8"		M8	100	25
31-36	Φ 35	1"	1 3/8"		M8	100	10
38-44	Φ 42	1 1/4"	1 5/8"		M8-M10	60	10
46-52		1 1/2"	1 7/8"	Φ 50	M8-M10	50	10
53-59	Φ 54		2 1/8"		M8-M10	40	5
59-66	Φ 64	2"	2 3/8"	Φ63	M8-M10	40	5
74-81	Φ 76	2 1/2"	3"	Φ75	M8-M10	30	-
90-94	Φ 89	3"	3 9/16"		M8-M10	25	-

**ΠΙΝΑΚΑΣ ΘΡΑΥΣΗΣ
10521, 10522 & 10523**

Μέγεθος Size	Όριο θραύσης Breaking load (KN)	Συνιστώμενο φορτίο Recommended load (KN)
3/8-1	3.9	1.3
1 1/4-2	4.8	1.6
2 1/2-3	6.9	2.3