ΗΛΕΚΤΡΙΚΕΣ ΣΕΓΕΣ ΚΟΠΗΣ ΣΩΛΗΝΩΝ

REMS Cat ANC

Universal electric reciprocating saw

895238A 1/1

Powerful, handy electric tool for universal free-hand sawing. Only 3.0 kg. Ideal for assembly, dismantling, repair.

Steel pipes and others	$ extsf{Ø} \leq$ 6", 160 mm
Other metal profiles,	
nail-embedded wood, pallets	≤ 250 mm
Plunge-in sawing for plastic pipes	$\emptyset \le 1600 \text{ mm}$

REMS saw blades, for other makes also, see page 48-49.

REMS Cat ANC VE – saws anything, anywhere. Extremely versatile and powerful.

Universal use

Ready for use anywhere, free-hand, overhead, in confined areas, flush to wall. Extremely versatile and efficient, particularly for metal. Saws metal pipes, boilers, tanks, bath tubs, window frames, etc., for rescue and disaster service operations.

Execution

Robust, job site-proven. Slender, handy design. Super light, only 3.0 kg. Ergonomically shaped front housing grip with slip resistant, heat insulating protection cover with soft grip, for forceful feed forward. Proven D-shaped handle. Flexible supporting shoe for secure guidance of saw. High sliding silicone gasket protects gear against water and dust. Powerful universal motor with ample reserve capacity, 1050 W. Safety tip switch.

Sturdy, square lift rod (Patent DE 34 48 345)

In special solid steel, mounted precisely in needle bearings towards the force direction and along the complete stroke length, for distortion-free, precise cutting also during tough use. For extremely long service life.

Oscillating drive with ANC

New type, super stable, water and dust resistant, maintenance-free oscillating drive for simultaneous generation of sawing stroke and orbital action of lift rod and saw blade. Allround needle bearing mounted crank drive (ANC) reduces friction, heat generation, wear. For long service life of drive also at extreme sawing

Vario-Electronic

Electronic stepless speed control of drive unit for sensitive start sawing and for speed selection during sawing. The speed is controlled by pressing the tip switch steplessly from 0 to 2200 rpm (acceleration switch).

Aggressive orbital action

Agressive orbital action by vertical hacking motion of saw blade provides forceful, fast forward feed, excellent chip flow and long service life of saw blades. Fixed orbital action, running in needle bearings, ensures long-lasting and forceful sawing also during extreme load conditions, e.g. sawing of steel pipe.

Universal saw blade clamp (Patent DE 3428445)

All saw blades - with universal or double tang - can be clamped without changing or turning the saw blade thrust piece.

REMS universal saw blade

Instead of many different saw blades, only 1 universal saw blade required. Highly flexible, also for sawing flush to the wall. Exceptionally wide clamping face by double tang mounting to ensure accurate seating and high stability. Alternating tooth pattern (combo-toothing) for rapid and smooth cutting. Long service life. (page 49).



Supply format

REMS Cat ANC VE. Electric universal reciprocating saw with Vario-Electronic (VE) for free-hand sawing up to 6", 250 mm. Drive unit with D-shaped handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful universal motor 230 V or 110 V, 50-60 Hz, 1050 W, safety tip switch. Electronic stepless speed control (acceleration switch). Universal saw blade clamp. Hexagon key. 1 REMS universal saw blade 150 mm. In cardboard box.

ArtNo.	
560030	

Accessories

Description	ArtNo.
REMS saw blades see page 49.	
Steel case	566005







