


ΗΛΕΚΤΡΟΚΙΝΗΤΕΣ ΒΑΛΒΙΔΕΣ ΒΕΛΙΜΟ

4456 Κ.Ε.47	Βαρέως τύπου 2-οδες Βαλβίδες Έδρας 120°C 2 θέσεων ON-OFF 24VDC ή 230VAC (8" & 10":230Vac)		
	Κωδ.	Διάμετρος	
	445650H	65 mm	1252,35
	445651H	80 mm	1521,80
	445652H	100 mm	2504,70
	445653H	125 mm	3658,38
	445654H	150 mm	4354,13
	445655H	200 mm	14994,10
	445656H	250 mm	20079,40
Σελίδα τεχν.καταλόγου			6.88

4456 Κ.Ε.47	Βαρέως τύπου 2-οδες Βαλβίδες Έδρας 120°C 2 θέσεων ON-OFF 24VDC ή 230VAC		
	Κωδ.	Διάμετρος	
	445650L	65 mm	1215,32
	445651L	80 mm	1484,77
	445652L	100 mm	2504,70
	445653L	125 mm	3658,38
	445654L	150 mm	4354,13
Σελίδα τεχν.καταλόγου			6.88

4456 Κ.Ε.47	Βαρέως τύπου 2-οδες Βαλβίδες Έδρας 120°C Αναλογικές H6..PN16- 24VDC		
	Κωδ.	Διάμετρος	
	445650M	65 mm	1242,92
	445651M	80 mm	1512,37
	445652M	100 mm	2566,69
	445653M	125 mm	3720,37
	445654M	150 mm	4416,12
	445655M	200 mm	16251,50
	445656M	250 mm	21336,80
Σελίδα τεχν.καταλόγου			6.88

4457 Κ.Ε.47	Βαρέως τύπου 3-οδες Βαλβίδες Έδρας 120°C 2 θέσεων ON-OFF 24VDC ή 230VAC (8" & 10":230Vac)		
	Κωδ.	Διάμετρος	
	445750H	65 mm	1187,84
	445751H	80 mm	1426,92
	445752H	100 mm	2427,54
	445753H	125 mm	3671,03
	445754H	150 mm	4259,26
	445755H	200 mm	17659,50
	445756H	250 mm	24021,10
Σελίδα τεχν.καταλόγου			6.88

4457 Κ.Ε.47	Βαρέως τύπου 3-οδες Βαλβίδες Έδρας 120°C 2 θέσεων ON-OFF 24VDC ή 230VAC (8" & 10":230Vac)		
	Κωδ.	Διάμετρος	
	445750L	65 mm	1150,81
	445751L	80 mm	1389,89
	445752L	100 mm	2427,54
	445753L	125 mm	3671,03
	445754L	150 mm	4259,26
Σελίδα τεχν.καταλόγου			6.88

4457 Κ.Ε.47	Βαρέως τύπου 3-οδες Βαλβίδες Έδρας 120°C Αναλογικές H7..PN16- NV24A-SR-TCP / GV12-24-SR-T		
	Κωδ.	Διάμετρος	
	445750M	65 mm	1178,41
	445751M	80 mm	1417,49
	445752M	100 mm	2489,53
	445753M	125 mm	3733,02
	445754M	150 mm	4321,25
	445755M	200 mm	18916,90
	445756M	250 mm	25278,50
Σελίδα τεχν.καταλόγου			6.88

4457 Κ.Ε.47	Βαρέως τύπου 2-οδες Βαλβίδες Έδρας 150°C Αναλογικές H6..PN16 - 24VDC		
	Κωδ.	Διάμετρος	
	445764M	15 mm	762,80
	445765M	20 mm	790,63
	445766M	25 mm	956,34
	445767M	32 mm	1047,42
	445768M	40 mm	1170,13
	445769M	50 mm	1471,20
	445770M	65 mm	2185,93
	445771M	80 mm	2352,91
	445781M	SP 80 mm	K.Z.
	445772M	100 mm	5715,28
	445773M	125 mm	8384,43
	445774M	150 mm	10531,10
Σελίδα τεχν.καταλόγου			6.88