





# Thermostatic Wafer Steam Trap

**Stainless Steel**

For Pressures to 250 psig (17 barg)...Cold Water Start-Up Capacities to 1 000 lb/hr (453 kg/hr)



**CHRYSSAFIDIS**



Model WMT-1 Trap

## Description

The WMT thermostatic wafer traps are designed to last longer than other oversized, all-purpose thermostatic and thermodynamic steam traps.

A water seal prevents loss of steam through the orifice of the WMT Series.

Adjusts automatically to flow rates, including large start-up loads, at all pressures within its range.

## Specification

Thermostatic wafer steam trap, type WMT stainless steel.

## How to Order

- Specify model number
- Specify size and type of pipe connection. When flanges are required, specify type of flange in detail

For a fully detailed certified drawing, refer to CD #1017 (WMT-1).

Model WMT-Series Thermostatic Wafer Trap Capacity							
Differential Pressure*		Cold Water Start-Up 70°F (21°C)		Hot Water Start-Up 212°F (100°C)		Operating Condensate 50°F (28°C) Below Saturation	
psig	barg	lb/hr	kg/hr	lb/hr	kg/hr	**lb/hr	**kg/hr
5	0.35	120	54	100	45	10	4.5
10	0.70	150	68	170	77	13	5.9
20	1.4	320	145	250	113	18	8.2
30	2	390	177	300	136	20	9.1
40	3	420	191	350	159	24	10.9
50	3.5	490	222	400	181	26	11.8
75	5	570	259	480	218	30	13.6
100	7	650	295	580	263	35	15.9
150	10.5	700	318	700	318	40	18.1
200	14	900	408	800	363	46	20.9
250	17	1 000	454	950	431	50	22.7

\*Capacities based on differential pressure with no back pressure.

\*\*Capacities will vary with the degree of subcooling. When greater capacities are required, the trap will automatically adjust to the load, up to the maximum (cold water) capacity shown, by increasing the amount of subcooling.

## WMT Thermostatic Wafer Steam Trap

Model No.	WMT-1			
Pipe Connections	in	mm	in	mm
"A" (Diameter)	1/4, 3/8	6, 10	1/2	15
"B" (Height)	2-1/4	57	2-1/4	57
Weight lb (kg)	3-5/16	84	3-5/16	84
	1-1/4 (0.6)		1-1/4 (0.6)	

Model	WMT-1
Connections	Screwed NPT and BSPT
Material	
Cap and body	ASTM A240 Grade 304L
Capsule	All stainless steel—304
Maximum Operating Conditions	
Maximum allowable pressure (vessel design)	250 psig @ 400°F (17 barg @ 204°C)
Maximum operating pressure	250 psig (17 barg)